

TF 160™

Welding



STANDARD	BACKREST	
	2" height adjustment «Floating without interval »	
	Backrest adjustment range 12" à 14"	
	Ergonomic padded backrest (12,75"w x 6,5"h)	
	SEAT	
	High resilience velva foam	
	Profiled seat (19,75"w x 16"d x 2"h)	
	SEAT HEIGHT ADJUSTMENT	
	Cylinder 200 mm (20,5"-28,5")	
	MECHANISM	
Seat angle adjustment		
Seat height adjustment		
BASES		
28" industrial steel		
20" footrest (adjustable height)		
CASTERS / GLIDES		
3" rubber casters (slow rolling)		

OPTIONS	ARMREST	
	Standard: height and side adjustment, moves 2" forward and swivels	
	Standard: height and lateral adjustment, moves 2" forward	
	Fireproof: height, side adjustment and swivels	
	SEAT HEIGHT ADJUSTMENT	
	Options	
	Cylinder 270 mm (24"-34")	
	CASTERS / GLIDES	
	Options	
	3" rubber casters with brake (slow rolling)	
3" double rubber casters (fast rolling)		
3" double rubber casters with brake (fast rolling)		
2" glides		
3" glides		

OPTIONS ADDITIONNELLES	Memory foam (seat)
	Memory foam (backrest)
	32" industrial steel base
	24" footrest (adjustable height)
	Tool compartment (11"w x 6"d x 1"h)
	Tool compartment (19"w x 8"d x 1"h)